



Model 7400 Specifications

INDUSTRIAL RIDING SCRUBBER

Feature		
Scrubbing System		
Cleaning path with side brush	57-inch	1,450 mm
without side brush	45-inch	1,145 mm
Solution tank	70 gallon	265 liter
Cylindrical scrub head		
Speed	400 rpm	400 rpm
Down pressure weight (variable to)	400 lb	180 kg
Brush diameter (2)	11-inch	280 mm
Brush length (2)	45-inch	1,145 mm
Optional side brush		
Speed	210 rpm	210 rpm
Down pressure weight (variable to)	140 lb	65 kg
Brush diameter (2)	16-inch	405 mm
Recovery System		
Recovery tank	70 gallon	265 liter
Demisting chamber	34 gallon	129 liter
Vacuum fan speed	14,000 rpm	14,000 rpm
Vacuum water lift	45-inch	1,145 mm
Propelling System		
Propel speed forward (variable to)	8.0 mph	12.9 km/h
Propel speed reverse (variable to)	4.0 mph	6.4 km/h
Engine-gasoline/LPG	55 hp GM	41 kW GM
Engine-diesel	37.5 hp Kubota	28 kW Kubota
Gradeability		
Transport at gross weight	8 deg/14.1%	8 deg/14.1%
Working (scrubbing)	6 deg/10.5%	6 deg/10.5%
Machine Dimensions		
Length	97-inch	2,465 mm
Width	60-inch	1,525 mm
With optional side brush	63-inch	1,600 mm
Rear squeegee	60-inch	1,525 mm
Height	58-inch	1,475mm
With overhead guard	80.5-inch	2,045 mm
Weight	3,299 lb	1,495 kg
Minimum aisle turn	125.5-inch	3,185 mm
Warranty	Please refer to your local Tennant representative for information.	